



## ApolloLED ECO



This product is used for the mobile illumination of large areas and/or intensive spatial lighting. Many uses also include the illumination of sports areas, such as ski slopes/cross-country ski trails and similar.

### Features light

- very powerful lighting
- robust design - illuminant cannot splinter or break
- the air in- and outlet are at the bottom of the lamp
- operation with permanent forced ventilation for high durability
- also usable as suspended lamp (without tripod)
- over-temperature circuit-breaker with independent reactivation
- full power immediately after switching on
- no preheating time, no cooling time
- operation with integrated power supply unit
- light all around at higher light point

### Technical data

Input voltage:	100 - 277 VAC
System performance:	300 W
Luminous flux:	32'321 lm
LED power:	100 lm/W incl. fan
Light colours:	5'000 K
Operating life:	> 50'000 h
Protection category:	IP44
Protection class:	I
Operating range of temperature:	-25° C to +50° C
Measurements LxD:	600 x 208 mm
Weight:	7.5 kg
Utilisation height:	2.7 m
Illumination area:	> 600 m <sup>2</sup>

### Technical data transport bag

Is offered completely with transport bag.	
Dimensions (LxD):	650 x 210 mm
Weight:	0.3 kg

### Technical data tripod

A matching tripod is recommended to guarantee optimum handling. It offers good characteristics, solid construction and precision workman-ship.

Dimensions	
– height extended:	2'400 mm
– diameter/base circle:	1'280 mm
Maximum load:	50 kg
Weight:	9.4 kg



Item no.	Designation
✓ 184857	ApolloLED ECO, 230 V, 300 W, 32'321 lm incl. feed-in cable 5 m 3 x 1.5 mm <sup>2</sup> , plug T13, incl. transport bag

Accessori/Pezzi di ricambio	
✓ 184858	Tripod to ApolloLED ECO
184860	ApolloLED ECO transport bag
184862	Tripod mount (inclination up to maximum 45°)
✓ 800444	Connection cable 5 m, 3 x 1.5 mm <sup>2</sup> , plug type 13
800445	Connection cable 10 m, 3 x 1.5 mm <sup>2</sup> , plug type 13



Item no. 184860



Item no. 184862



Item no. 184858

✓ from stock, offer subject to prior sale

1/1

**GIFAS**  
ELECTRIC

GIFAS-ELECTRIC GmbH  
Dietrichstrasse 2  
CH-9424 Rheineck

+41 71 886 44 44  
+41 71 886 44 49  
info@gifas.ch  
www.gifas.ch